

PHILIPS

Lighting



TL-D 标准颜色

TL-D 58W/54-765 1SL/25

低压汞放电灯，带有一个 26mm 的管状包层。

安全提示

· A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


产品数据

基本信息	
底座	G13 [Medium Bi-Pin Fluorescent]
10% 故障条件下的使用寿命 (标称)	10000 h
50% 故障条件下的使用寿命 (标称)	13000 h
照明科技	
颜色代码	54-765
光通量 (标称)	4000 lm
颜色名称	冷日光
10000 小时下的光通维持率 (标称)	75 %
2000 小时下的光通维持率 (标称)	90 %
5000 小时下的光通维持率 (标称)	80 %
相关色温 (标称)	6200 K
显色指数 (标称)	72
运营和电气	
Power (Rated) (Nom)	58.5 W
灯具电流 (标称)	0.670 A
电压 (标称)	111 V
控制调光	
可调光	是

机械和壳体	
灯泡外形	T8 [26 mm (T8)]
应用	
汞 (Hg) 含量 (标称)	8.0 mg
能耗 kWh/1000 h	68 kWh
产品参数	
完整产品代码	692234199605400
订单产品名称	TL-D 58W/54-765 1SL/25
EAN/UPC - 产品	6922341996054
订购代码	928049005453
SAP 计算器 - 每个包中的数量	1
计算器 - 每个外包装箱中的包数	25
SAP 材料	928049005453
SAP 净重 (每件)	0.230 kg
ILCOS 代码	FD-58/62/2A-E-G13

TL-D 标准颜色


二维绘图




TL-D 58W/54-765

Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL-D 58W/54-765	28 mm	1500.0 mm	1507.1 mm	1504.7 mm	1514.2 mm
1SL/25					

光度数据




LDPB_TL-DSTD_54-765-Spectral power distribution B/W




LDPO_TL-DSTD_54-765-Spectral power distribution Colour

寿命




LDLE_TL-DSTD_0001-Life expectancy diagram



LDLE_TL-DSTD_0002-Life expectancy diagram

TL-D 标准颜色

寿命



LDLM_TL-DSTD_0001-Lumen maintenance diagram

