



MASTER PL-C 4 针

MASTER PL-C 13W/840/4P 1CT/5X10BOX

紧凑型节能荧光灯紧凑的长弧结构，低压低汞荧光灯管由 4 根平行的细荧光灯管组成

安全提示

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

产品数据

基本信息	
底盖	G24Q-1 [G24q-1]
50% 故障预热条件下的使用寿命 (标称)	13000 h
LSF 预热 2000 小时额定	99 %
LSF 预热 4000 小时额定	98 %
LSF 预热 6000 小时额定	97 %
LSF 预热 8000 小时额定	90 %
照明科技	
颜色代码	840 [CCT 4000K]
光通量 (标称)	925 lm
光通量 (额定) (标称)	925 lm
颜色名称	冷白色 (CW)
相关色温 (标称)	4000 K
光效 (额定) (标称)	69 lm/W
显色指数 (标称)	82
LLMF 2000 小时额定	92 %
LLMF 4000 小时额定	87 %


LLMF 6000 小时额定	83 %
LLMF 8000 小时额定	81 %
运营和电气	
Power (Rated) (Nom)	13.0 W
灯具电流 (标称)	0.170 A
温度	
设计温度 (标称)	28 °C
控制调光	
可调光	是
机械和壳体	
底盖信息	4P
应用	
汞 (Hg) 含量 (标称)	1.4 mg

MASTER PL-C 4 针

能耗 kWh/1000 h	15 kWh
产品参数	
完整产品代码	871150062332400
订单产品名称	MASTER PL-C 13W/840/4P 1CT/5X10BOX
EAN/UPC - 产品	8711500623324
订购代码	927907184002

SAP 计算器 - 每个包中的数量	1
计算器 - 每个外包装箱中的包数	50
SAP 材料	927907184002
SAP 净重 (每件)	49.900 g
ILCOS 代码	FSQ-13/40/1B-E-G24q=1


二维绘图




PL-C 13W/840/4P

Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 13W/840/4P 1CT/5X10BOX	27.1 mm	27.1 mm	97.5 mm	117.0 mm	131.9 mm

光度数据




LDPB_PLC4P_840-Spectral power distribution B/W



LDPO_PLC4P_840-Spectral power distribution Colour


MASTER PL-C 4 针

寿命



LDLE_PLC4P_0001-Life expectancy diagram

LDLE_PLC4P_0002-Life expectancy diagram



LDLM_PLC4P_0001-Lumen maintenance diagram

