



MASTER PL-C 4 针

MASTER PL-C 26W/865/4P 1CT/5X10BOX

紧凑型节能荧光灯;紧凑的长弧结构, 低压低汞荧光灯管;由 4 根平行的细荧光灯管组成

安全提示

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

产品数据

基本信息	
底盖	G24Q-3 [G24q-3]
50% 故障预热条件下的使用寿命 (标称)	13000 h
LSF 预热 2000 小时额定	99 %
LSF 预热 4000 小时额定	98 %
LSF 预热 6000 小时额定	97 %
LSF 预热 8000 小时额定	90 %
照明科技	
颜色代码	865 [CCT 6500K]
光通量 (标称)	1740 lm
光通量 (额定) (标称)	1740 lm
颜色名称	冷日光
相关色温 (标称)	6500 K
光效 (额定) (标称)	66 lm/W
显色指数 (标称)	80
LLMF 2000 小时额定	90 %
LLMF 4000 小时额定	85 %


LLMF 6000 小时额定	81 %
LLMF 8000 小时额定	77 %
运营和电气	
Power (Rated) (Nom)	26.0 W
灯具电流 (标称)	0.335 A
温度	
设计温度 (标称)	28 °C
控制调光	
可调光	是
机械和壳体	
底盖信息	4P
应用	
汞 (Hg) 含量 (标称)	1.4 mg

MASTER PL-C 4 针

能耗 kWh/1000 h	29 kWh
产品参数	
完整产品代码	871869960689300
订单产品名称	MASTER PL-C 26W/865/4P 1CT/5X10BOX
EAN/UPC - 产品	8718699606893
订购代码	927907386565

SAP 计算器 - 每个包中的数量	1
计算器 - 每个外包装箱中的包数	50
SAP 材料	927907386565
复制净重 (每件)	60.400 g



二维绘图



Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 26W/865/4P 1CT/5X10BOX	27.1 mm	27.1 mm	130.5 mm	149.0 mm	163.9 mm

MASTER PL-C 26W/865/4P 1CT/5X10BOX

光度数据





LDPB_PLC4P_865-Spectral power distribution B/W

LDPO_PLC4P_865-Spectral power distribution Colour

MASTER PL-C 4 针

寿命



LDLE_PLC4P_0001-Life expectancy diagram

LDLE_PLC4P_0002-Life expectancy diagram



LDLM_PLC4P_0001-Lumen maintenance diagram

