



MASTER TL-D 90 Graphica

MASTER TL-D 90 Graphica 36W/965 SLV/10

低压汞放电灯，配备管状 26 毫米的封装。

安全提示

· A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

产品数据

运营和电气	
功耗	36.8 W
灯具电流 (标称)	0.440 A
基本信息	
底盖	G13 [Medium Bi-Pin Fluorescent]
通量测量参考	Sphere
照明科技	
颜色代码	965 [CCT of 6500K]
光通量	2,100 lm
颜色名称	冷日光
色度坐标 X (标称)	0.313
色度坐标 Y (标称)	0.337
相关色温 (标称)	6500 K
光效 (额定) (标称)	57.1 lm/W
显色指数 (CRI)	97

控制调光	
可调光	是
机械和壳体	
灯泡外形	T8 [26 毫米 (T8)]
应用	
能效等级	G
汞 (Hg) 含量 (标称)	1.7 mg
能耗 kWh/1000 h	37 kWh
EPREL 注册号	423,528
产品参数	
Full EOC	871150088836525
订单产品名称	MASTER TL-D 90 Graphica 36W/965 SLV/10
订购代码	928044796581
SAP 计算器 - 每个包中的数量	1
计算器 - 每个外包装箱中的包数	10
材料编号 (12NC)	928044796581


MASTER TL-D 90 Graphica

完整的产品名称	MASTER TL-D 90 Graphica 36W/965 SLV/10
EAN/UPC - 案例	8711500888662

二维绘图



Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D 90 Graphica 36W/965 SLV/10	28 mm	1,199.4 mm	1,206.5 mm	1,204.1 mm	1,213.6 mm

光度数据



Spectral Power Distribution Colour - MASTER TL-D 90 Graphica 36W/965 SLV/10

寿命




Life Expectancy Diagram - MASTER TL-D 90 Graphica 36W/965 SLV/10

Life Expectancy Diagram - MASTER TL-D 90 Graphica 36W/965 SLV/10

MASTER TL-D 90 Graphica

寿命



Lumen Maintenance Diagram - MASTER TL-D 90 Graphica 36W/965 SLV/10

