



MASTERColour CDM-T 精锐型

MASTERC CDM-T Elite 50W/942 G12 1CT

单端高光效陶瓷金属卤化物放电灯

安全提示

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Use only with electronic control gear. 35W & 70W lamps may also use electromagnetic gear.
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

产品数据

基本信息	
底盖	G12 [G12]
操作位置	UNIVERSAL [任意或通用 (U)]
通量测量参考	Sphere

照明科技	
颜色代码	942 [CCT of 4200K]
光通量	5,000 lm
颜色名称	冷白色 (CW)
色度坐标 X (标称)	0.371
色度坐标 Y (标称)	0.366
相关色温 (标称)	4200 K
光效 (额定) (标称)	5,000 lm/W
显色指数 (CRI)	90

运营和电气	
功耗	50.2 W
电压 (标称)	91 V
电压 (标称)	91 V

控制调光	
可调光	否

机械和壳体	
灯泡外观	透明
灯泡外形	T19 [T 19 毫米]


应用	
能效等级	F
汞 (Hg) 含量 (最高)	5.7 mg

MASTERC colour CDM-T 精锐型

汞 (Hg) 含量 (标称)	5.7 mg
能耗 kWh/1000 h	51 kWh
EPREL 注册号	1,519,238
产品参数	
Full EOC	871829120159500
订单产品名称	MASTERC CDM-T Elite 50W/942 G12 1CT
订购代码	928080015131




SAP 计算器 - 每个包中的数量	1
计算器 - 每个外包装箱中的包数	12
材料编号 (12NC)	928080015131
完整的产品名称	MASTERC CDM-T Elite 50W/942 G12 1CT
EAN/UPC - 案例	8718291201601

二维绘图



Product	D (max)	O	L (min)	L (max)	L	C (max)
MASTERC CDM-T Elite 50W/942 G12 1CT	20 mm	7.1 mm	55 mm	57 mm	56 mm	103 mm

光度数据




Light Distribution Diagram - MASTERC CDM-T Elite 50W/942 G12 1CT

Spectral Power Distribution Colour - MASTERC CDM-T Elite 50W/942 G12 1CT

MASTERC colour CDM-T 精锐型

寿命



Life Expectancy Diagram - MASTERC CDM-T Elite 50W/942 G12 1CT

Lumen Maintenance Diagram - MASTERC CDM-T Elite 50W/942 G12 1CT

