



# Essential LEDtube

## LEDtube 600mm 8W 765 T8 CN I

Essential LEDtube is an affordable LED tube that is suitable for replacing T8 fluorescent lamps. The product provides a natural lighting effect for use in general lighting applications, as well as instant energy savings – an environmentally friendly solution.



### 产品数据

基本信息		电压 (标称)	
底盖	G13 [ Medium Bi-Pin Fluorescent]	220-240 V	
符合欧盟 RoHS 规范	是	温度	
标称寿命 (标称)	15000 h	环境温度 (最高)	45 °C
切换循环	50000X	环境温度 (最低)	-20 °C
照明科技		存放温度 (最高)	65 °C
颜色代码	765 [ CCT 6500K]	存放温度 (最低)	-40 °C
光束角度 (标称)	240 °	最大外壳温度 (标称)	60 °C
光通量 (标称)	800 lm	控制调光	
颜色名称	冷日光	可调光	否
相关色温 (标称)	6500 K	机械和壳体	
光效 (额定) (标称)	100.00 lm/W	产品长度	600 mm
颜色一致性	<6	灯泡外形	管, 双端
显色指数 (标称)	73	应用	
标称使用寿命结束时灯的光通维持率 (标称)	70 %	节能产品	Yes
运营和电气		适用于重点照明	No
输入频率	50 至 60 Hz	批准标志	RoHS compliance KEMA Keur certificate
Power (Rated) (Nom)	8 W	能耗 kWh/1000 h	8 kWh
启动时间 (标称)	0.5 s		
60% 灯光下的预热时间 (标称)	0.5 s		
功率系数 (标称)	0.5		





# Essential LEDtube

## 寿命




LEDtube 15K FailureRate

LEDtube 15K



LEDtube 15K LumenVsTc

LEDtube 15K LifetimeVsTc



LEDtube 15K

## Essential LEDtube

