



Essential LEDtube

CorePro LEDtube 600mm 8W865 G5 I APR

Essential LEDtube is an affordable LED tube that is suitable for replacing T8 fluorescent lamps. The product provides a natural lighting effect for use in general lighting applications, as well as instant energy savings – an environmentally friendly solution.

产品数据

基本信息		60% 灯光下的预热时间 (标称)	
底盖	G5 [G5]	功率系数 (标称)	0.92
符合欧盟 RoHS 规范	是	电压 (标称)	100-240 V
标称寿命 (标称)	30000 h	温度	
切换循环	50000X	环境温度 (最高)	45 °C
照明科技		环境温度 (最低)	-20 °C
颜色代码	865 [CCT 6500K]	存放温度 (最高)	65 °C
光束角度 (标称)	200 °	存放温度 (最低)	-40 °C
光通量 (标称)	1050 lm	最大外壳温度 (标称)	70 °C
颜色名称	冷日光	控制调光	
相关色温 (标称)	6500 K	可调光	否
光效 (额定) (标称)	131.00 lm/W	机械和壳体	
颜色一致性	<6	产品长度	600 mm
显色指数 (标称)	80	灯泡外形	管, 双端
标称使用寿命结束时灯的光通维持率 (标称)	70 %	应用	
运营和电气		节能产品	Yes
输入频率	50 至 60 Hz	批准标志	标志 RoHS compliance KEMA Keur certificate
Power (Rated) (Nom)	8 W	能耗 kWh/1000 h	8 kWh
灯具电流 (最大)	89 mA		
灯具电流 (最小)	39 mA		
启动时间 (标称)	0.5 s		


Essential LEDtube

产品参数

完整产品代码	871869673200700
订单产品名称	CorePro LEDtube 600mm 8W865 G5 I APR
EAN/UPC - 产品	8718696732007
订购代码	929001380808
SAP 计算器 - 每个包中的数量	1

计算器 - 每个外包装箱中的包数	20
SAP 材料	929001380808
Copy Net Weight (Piece)	0.070 kg


二维绘图




CorePro LEDtube 600mm 8W865 G5 I APR

Product	D1	D2	A1	A2	A3
CorePro LEDtube 600mm 8W865 G5 I APR	15.8 mm	19 mm	549 mm	556.1 mm	563.2 mm


光度数据



ESSENTIAL LEDtube 8W G5 865 APR





ESSENTIAL LEDtube 8W G5 865 APR



ESSENTIAL LEDtube 8W G5 840 APR



Essential LEDtube

寿命




ESSENTIAL LEDtube 8-16W G5 830-865 APR

ESSENTIAL LEDtube 8-16W G5 830-865 APR



ESSENTIAL LEDtube 8-16W G5 830-865 APR

ESSENTIAL LEDtube 8-16W G5 830-865 APR



ESSENTIAL LEDtube 8W G5 830-865 APR

Essential LEDtube

