



Essential LEDtube

CorePro LEDtube 1200mm 16W865 G5 I APR

Essential LEDtube is an affordable LED tube that is suitable for replacing T8 fluorescent lamps. The product provides a natural lighting effect for use in general lighting applications, as well as instant energy savings – an environmentally friendly solution.

产品数据

基本信息		60% 灯光下的预热时间 (标称)	
底盖	G5 [G5]		0.5 s
符合欧盟 RoHS 规范	是	功率系数 (标称)	0.92
标称寿命 (标称)	30000 h	电压 (标称)	100-240 V
切换循环	50000		
照明科技		温度	
颜色代码	865 [CCT 6500K]	环境温度 (最高)	45 °C
光束角度 (标称)	200 °	环境温度 (最低)	-20 °C
光通量 (标称)	2100 lm	存放温度 (最高)	65 °C
颜色名称	冷日光	存放温度 (最低)	-40 °C
相关色温 (标称)	6500 K	最大外壳温度 (标称)	70 °C
光效 (额定) (标称)	131.00 lm/W		
颜色一致性	<6	控制调光	
显色指数 (标称)	80	可调光	否
标称使用寿命结束时灯的光通维持率 (标称)	70 %		
运营和电气		机械和壳体	
输入频率	50 至 60 Hz	产品长度	1200 mm
Power (Rated) (Nom)	16 W	灯泡外形	管, 双端
灯具电流 (最大)	179 mA		
灯具电流 (最小)	77 mA	应用	
启动时间 (标称)	0.5 s	节能产品	Yes
		批准标志	标志 RoHS compliance KEMA Keur certificate
		能耗 kWh/1000 h	16 kWh


Essential LEDtube

产品参数

完整产品代码	871869673206900
订单产品名称	CorePro LEDtube 1200mm 16W865 G5 I APR
EAN/UPC - 产品	8718696732069
订购代码	929001381108
SAP 计算器 - 每个包中的数量	1

计算器 - 每个外包装箱中的包数	20
SAP 材料	929001381108
复制净重 (每件)	0.124 kg



二维绘图



CorePro LEDtube 1200mm 16W865 G5 I APR


Product	D1	D2	A1	A2	A3
CorePro LEDtube 1200mm 16W865 G5 I APR	15.8 mm	19 mm	1149 mm	1156.1 mm	1163.2 mm

光度数据



ESSENTIAL LEDtube 16W G5 865 APR



ESSENTIAL LEDtube 8W G5 865 APR



ESSENTIAL LEDtube 16W G5 840 APR



Essential LEDtube

寿命




ESSENTIAL LEDtube 8-16W G5 830-865 APR

ESSENTIAL LEDtube 8-16W G5 830-865 APR



ESSENTIAL LEDtube 8-16W G5 830-865 APR

ESSENTIAL LEDtube 8-16W G5 830-865 APR



ESSENTIAL LEDtube 16W G5 830-865 APR

Essential LEDtube

